

General information

Antenna covering NB-IoT Band 8 and 20 (791 - 960 MHz), GSM 900 (880 - 960 MHz), GSM 1800 and 1900 (1710 - 1990 MHz) for inside mounting on non-conductive surfaces such as plastic.

InSide GSM/NB-IoT is a ground plane independent antenna including coaxial cable with MHF or MHF4 connector, supplied with adhesive.




Technical data

Frequency	791 - 960, 1710 - 1990 MHz
Return loss*	< -7.7 dB, 791 - 960 MHz < -4.5 dB, 1710 - 1990 MHz
Efficiency*	> -1.8 dB (66%), 791 - 960 MHz > -5.9 dB (26%), 1710 - 1990 MHz
Gain*	Max 4.1 dBi, 791 - 960 MHz Max 2.8 dBi, 1710 - 1990 MHz
Dimension	8.00 x 75.00 mm, thickness 0.80 mm
RoHS status	Compliant with EU directive 2011/65/EU and 2015/863
Mounting	Adhesive tape
Temperature	-40 to +85° C

Applications

IoT-devices
M2M-communications
Telemetry
Automated meter reading
Alarms




Antenna drawing. Above dimensions are given in millimeter.


*Measured on Proant standard measurement fixture, see next page for more information.

Electrical performance

Measurement setup




Return loss




The antenna measurements were done on Proant's standard measurement fixture - the antenna mounted in an ABS plastic box, 150x150x45 mm, connected to a PCB, 120x50 mm, with the cable fully extended.







Total radiation efficiency









Maximum radiation gain



Radiation pattern, 870 MHz



Radiation pattern, 1850 MHz



Intended applications

The antenna is optimized for pentaband operation in the GSM, UMTS and NB-IoT systems, which is defined by several frequency bands. Some of the supported bands are:

GSM/GPRS/EDGE	GSM 850 (824 – 894 MHz)
	GSM 900 (880 – 960 MHz)
	GSM 1800 (1710 – 1880 MHz)
	GSM 1900 (1850 – 1990 MHz)
UMTS/LTE	Band 2 (1850 – 1990 MHz)
	Band 3 (1710 – 1880 MHz)
	Band 5 (824 – 894 MHz)
	Band 6 (830 – 883 MHz)
	Band 8 (880 – 960 MHz)
LoRa	EU 863-870 MHz
	US 902-928 MHz
	AU 915-928 MHz
Sigfox	868 MHz
NB-IoT	Band 8 (880 - 960 MHz)
	Band 20 (791 - 862 MHz)

Ordering information

Part number	Part name	Details
PRO-IS-573	InSide GSM/NB-IoT, 60 mm MHF	Antenna for NB-IoT and GSM. 60 mm cable with MHF (U.FL) connector.
PRO-IS-589	InSide GSM/NB-IoT, 64 mm MHF4	Antenna for NB-IoT and GSM. 64 mm cable with MHF4 connector.

For information on sales, delivery terms and conditions and prices, please visit the Proant website (www.proant.se) for a complete list of distributors.

Proant offers consultation with design-in of the InSide antennas. Proant have all necessary capabilities for antenna design including anechoic chamber and prototype workshop. Please send your requests to info@proant.se.

Disclaimer

The information given in this application note shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Proant AB hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of intellectual property rights of any third party.